

# Dehumidifier

## Consecutive Drainage Function

Free of the hassle of pouring water away yourself.

## 5°C Low Temperature Operation

Operate finely at 5°C, making you enjoy fresh air under any environment.



0.5 W Standby



Water Full Indicator



Self-diagnosis



External Drain Connector



Healthy Filters



Real-time Display of Ambient Humidity



Water Level Display



Water Overflow Protection



Filter Cleaning Reminder

Features: ● Standard ● Optional

Model		GDN12AH-K4EBB1A	GDN20AH-K4EBB1A
Dehumidifying Volume	L/D	12	20
Power Supply	Ph, V, Hz	1Ph, 220-240V, 50Hz	1Ph, 220-240V, 50Hz
Power Input	W	220	330
Power Current	A	1.1	1.7
Rated Current	A	1.4	2.0
Airflow Volume	CMH	150	150
Sound Pressure Level	dB(A)	43	45
Water Tank Volume	L	3.6/4.0	3.6/4.0
Refrigerant		R134a	R134a
Outline Dimension (W×H×D)	mm	343×523×260	343×523×260
Package Dimension (W×H×D)	mm	396×315×555	396×315×555
Net/Gross Weight	Kg	12.5/13.5	14/15.5
Loading Qty (40'HQ)	Set	860	860

Zalka - Jawharji Street Tel: +961 4 710866 - 867  
E-mail: [acsons@cyberia.net.lb](mailto:acsons@cyberia.net.lb) Website: [www.greeac.com](http://www.greeac.com)