

Lomo R410A



Features: ● Standard ● Optional

Model			GWH09QB-K3NNB6B	GWH12QC-K3NNB6B	GWH18QD-K3NNB6B	GWH24QE-K3NNB6B
Fuction			Cooling & Heating	Cooling & Heating	Cooling & Heating	Cooling & Heating
Capacity	Cooling	Btu/h	9000	12000	18000	24000
	Heating	Btu/h	9500	13000	19000	25000
EER/COP		WW	3.05/3.48	3.33/3.98	3.11/3.41	3.29/4.06
Power Supply			220-240V~, 50Hz	220-240V~, 50Hz	220-240V~, 50Hz	220-240V~, 50Hz
Power Input	Cooling	W	865	1057	1698	2140
	Heating	W	800	958	1631	1805
Rated Current	Cooling	A	6.0	8.0	11.1	15.0
	Heating	A	6.2	8.0	10.0	15.0
Airflow Volume		Indoor	CMH	550	650	850
Indoor Unit						
Sound Pressure Level	Indoor	dB(A) (SH/H/M/L)	40/37/33/26	41/37/34/29	46/44/41/35	50/46/42/38/
Outline Dimension	WxHxD	mm	790x275x200	845x289x209	970x300x224	1078x325x246
Package Dimension	WxHxD	mm	866x271x367	921x281x379	1041x383x320	1148x413x350
Net Weight/Gross Weight		Indoor	Kg	8.5/10.5	10/12	13.5/16.5
Outdoor Unit						
Sound Pressure Level	Outdoor	dB(A)	48	49	54	54
Outline Dimension	WxHxD	mm	776x540x320	776x540x320	913x680x378	913x680x378
Package Dimension	WxHxD	mm	823x358x595	823x358x595	997x431x740	997x431x740
Net Weight/Gross Weight		Outdoor	Kg	30/32.5	29.5/32	47/51
Connection Pipe	Liquid	Inch	1/4	1/4	1/4	1/4
	Gas	Inch	3/8	1/2	1/2	5/8
Loading Capacity		40'HQ	Sets	262	242	150



Lomo R410A

