


Humanized Cold Air Prevention



Low ambient temperature heating of Gree I-Crown series



Low ambient temperature heating of conventional air con

Wide Ambient Operation Range

From -30°C to 54°C Ultra low ambient heating with 2-stage compressor. Operation sketch map of 2-Stage compressor.

Blue:


Low-pressure suction

Purple:

Medium-pressure inflation

Red:

High-pressure discharge



Three-dimensional Fan Blow

110cm vertical air outlet with big circulating air volume and wide air outlet angle. Provide more comfortable cooling and heating enjoyment.




E-Joy button

Combining the environmental sensor, you just need to press E-Joy button to realize auto regulation according to indoor temperature, humidity and air flow and provide users with utmost comfort.




Low Noise

Noise as low as 26dB(A)



5 kinds of Fan Speed

Designed with 5 kinds of fan mode



Model			GVH24AK-S3DTC5A
Function			
Capacity	Cooling	Btu/h	24566
	Heating	Btu/h	32414
EER/COP		W/W	3.41/3.06
Power Supply			
Power Input	Cooling	W	2110
	Heating	W	3100
Rated Current	Cooling	A	9.5
	Heating	A	14
Airflow Volume	Indoor	CMH	1200
Indoor Unit			
Sound Pressure Level	Indoor	dB(A)(SH/H/M/L)	46/43/36/33
Outline Dimension	WxHxD	mm	1796x509x476
Package Dimension	WxHxD	mm	1973x383x615
Net Weight/Gross Weight	Indoor	Kg	52/70
Outdoor Unit			
Sound Pressure Level	Outdoor	dB(A)	57
Outline Dimension	WxHxD	mm	955x700x396
Package Dimension	WxHxD	mm	1083x488x855
Net Weight/Gross Weight	Outdoor	Kg	63/68
Connection Pipe	Liquid	Inch	1/4
	Gas	Inch	5/8
Loading Capacity	40'HQ	Sets	56

