



Model			GVH24AG-K1NNA5A	GVH36AH-M1NNA5A	GVH48AH-M1NNA5A	GVH60AH-M1NTA5A
Fuction			Cooling & Heating	Cooling & Heating	Cooling & Heating	Cooling & Heating
Capacity	Cooling	Btu/h	24000	36000	48000	60000
	Heating	Btu/h	25000	37000	49000	61000
EER/COP		WW	2.66/3.13	2.58/2.67	2.52/2.82	2.47/2.83
Power Supply			220-240V~, 50Hz, 1P	380-415V~, 50Hz, 3P	380-415V~, 50Hz, 3P	380-415V~, 50Hz, 3P
Power Input	Cooling	W	2650	4089	4885	5800
	Heating	W	2470	3953	4476	6000
Rated Current	Cooling	A	17.9	10.6	11	9.8
	Heating	A	18.3	10.4	10.1	10.2
Airflow Volume	Indoor	CMH	1100	1850	1850	2000
Indoor Unit						
Sound Pressure Level	Indoor	dB(A) (SH/H/M/L)	48/45/42/40	52/50/47/44	52/50/47/44	54/52/50/47
Outline Dimension	WxHxD	mm	500x1757x300	1870x581x395	518x1870x395	581x1870x395
Package Dimension	WxHxD	mm	630x1940x435	2080x735x530	530x2080x367	2083x738x545
Net Weight/Gross Weight	Indoor	Kg	40/60	57/83	57/83	61/87
Outdoor Unit						
Sound Pressure Level	Outdoor	dB(A)	56	58	60	63
Outline Dimension	WxHxD	mm	1018x700x412	1050x840x410	1250x1032x412	1032x1250x412
Package Dimension	WxHxD	mm	1100x755x450	1100x880x450	1280x1110x450	1113x453x1400
Net Weight/Gross Weight	Outdoor	Kg	59/64	90/104	102/112	123/134
Connection Pipe	Liquid	Inch	3/8	1/2	1/2	1/2
	Gas	Inch	5/8	3/4	3/4	3/4
Loading Capacity	40'HQ	Sets	66	51	60	40

