


Fairy inverter



Model			GWH12ACB-K3NNA1A	GWH18ACD-K3DNA1A	GWH24ACE-K3DNA1A
Function			Cooling & Heating	Cooling & Heating	Cooling & Heating
Capacity	Cooling	Btu/h	12000	18000	24000
	Heating	Btu/h	13000	19000	25000
EER/COP		W/W	3.23/3.71	3.42/3.74	3.57/3.675
Power Supply			220-240V~, 50Hz	220-240V~, 50Hz	220-240V~, 50Hz
Power Input	Cooling	W	1084	1500	1876
	Heating	W	989	1410	1945
Rated Current	Cooling	A	6.9	10.9	16.42
	Heating	A	7.3	11.5	16.86
Airflow Volume		m3/h	660/540/460/330	800/760/690/570	1300/1200/950/850
Indoor Unit					
Sound Pressure Level	Indoor	dB(A)	45/39/34/29	47/45/41/37	50/46/42/38
Outline Dimension	WxHxD	mm	889×294×212	1013×307×221	1122×329×247
Package Dimension	WxHxD	mm	940×365×284	1080×378×315	1193×410×350
Net Weight/Gross Weight	Indoor	Kg	10.5/12.5	14/17	14/17
Outdoor Unit					
Sound Pressure Level	Outdoor	dB(A)	53	56	58
Outline Dimension	WxHxD	mm	776×540×320	955×700×396	955×700×396
Package Dimension	WxHxD	mm	823×595×358	1029×750×458	1029×750×458
Net Weight/Gross Weight	Outdoor	Kg	28/30.5	45/49.5	53/57.5
Connection Type	Liquid	Inch	1/4"	1/4"	1/4"
	Gaz	Inch	3/8"	1/2"	5/8"
Loading Capacity	40'HQ	Stes	211	125	111